



**READY FIRE**  
DETONATION NOW

**R-140S RDX**

**R-140 HMX**

**FEATURING**  
**IgniteRite™**  
**High Performance**  
**Wire**



Also available: R-85, Custom Dets

**IGNITERITE™**  
Ignition, activate.

**IgniteRite™ Leg Wires**

- Teflon insulated
- 22 Gauge Solid Copper
- High Temp
- 4Ft

Lead Wire

Resistance Module

Explosive

Tubular Shell

**Packaging**

- Weight 1.52 lbs Box of 10
- Outer Box (10 pack) 12 x 7.5 x 3 (LxWxH)
- Individual Box (1) 6 x 1.5 x .5 (LxWxH)
- Overpack available (100 M.O.Q.)



The R-140™ (HMX) and R-140S™ (RDX) detonator (blasting cap) is used by professionals to trigger an explosive device. These detonators can be chemically, mechanically, or electrically initiated, the latter two being the most common.

- Shell Length 32mm / 1.25"
- Base Charge 5 grains RDX (0.325 gram)
- No-Fire Current 0.2 amperes
- All-Fire Current 0.8 amperes
- Min Firing Current 0.5 amperes
- High Temp Performance 176C 350F 1hr
- Pressure Rating - 1hr 0.7MPa (100PSI)
- Fluid Disabling Hole
- Electrostatic Sensitivity Energy Value 781mJ
- Transport/Storage/Capability Class 1.4s
- Packaging: Antistatic sleeve and spark gap protection

Net Weight per DET no packaging - .3375 oz (9.57 grams)

PMR Global™  
4290 E. FM 1187  
Burleson, Texas 76028  
(817) 484-1100 Ext. 102

**PMRGLOBAL.COM**

